

PEACE ON THE ROAD





+50 years of expertise in manufacturing trailers and semitrailers



3 Manufacturing sites Sumaré/SP and Caxias do Sul/RS









Unidade I - Caxias do Sul - RS BR-116, 15675 - KM 146 95057-007 - São Ciro Fone: 55 (54) 3771-6400 Unidade II - Caxias do Sul - RS BR-116, 15354 - KM 146 95055-003 - De Lazzer Fone: 55 (54) 3771-6400

Unidade - Sumaré - SP Rodovia Anhanguera, KM 108,05 13181-030 Fone: 55 (19) 3770-2200



To know our **Product Line** and **Distributor Network**, access our website by scanning the following QR Code.

PEACE ON THE ROAD











TECHNICAL FEATURES

Base

Chassis made of high-strength steel 8.25x22.5" steel wheel Mechanical Suspension 1st axle air lift 2" flanged kingpin 100% LED electrical installation Mechanical lifting device ABS brake and Automatic brake compensator Polymeric Toolbox Water tank Supply box (Premium Model) Aluminum side protection Polymeric wraparound fender with mudguard

Cargo Box

Cargo box made of high-strength steel Upper hinge opening rear lid Internal chains Transversal tarpaulin bows Rubber lid seal Embedded side rail between columns Front and rear mooring rivets Front and side ladder Tarpaulin: Possibility of choosing colors Cargo box: Possibility to choose colors

COMPETITIVE DIFFERENTIALS

Wide-gauge chassis Increased stability and safety Reduced suspension and tire wear **Distributor Network** More than 35 service points throughout the country Modern and functional design Roller-free lid opening **100% LED electrical installation** Increased durability and safety 90x90 bearing and ventilated hub Increased brake lining service life Embedded side rail between columns It prevents material accumulation **Electrostatic powder-painted chassis** High-performance painting, superior quality finishing Increased durability and corrosion resistance Increased resistance to impacts (rocks) Uniform coverage UV protection Cargo box made of high-strength steel Increased durability and resistance Supply box - standard premium model Increased comfort and convenience for the driver Dump Road Train Model with Fifth Wheel Dolly or **Ball hitch**

TABLE

	DUMP	Volume	Accompl. TT	GCWR (ton)	Side Prof. (mm)	Floor Prof. (mm)	Approx. Tara Weight (Kg)
	SR BA AB - 3A (1+2) - (Sand and Gravel)	20m³	4X2	43 ton	3,00	3,00	6.970
	SR BA AB - 3A - (Sand and Gravel)	25m³	6X2	45 ton	4,75	4,75	7.480
	SR BA AB - 3A - (Sand and Gravel)	35m³	6X2	45 ton	3,00	4,75	7.750
	SR BA GR - 3A - (Side Kit Trailer)	40m ³	6X2	45 ton	3,00	3,00	7.690
	SR BA GR - 3A - (Side Kit Trailer)	45m³	6X2	48,5 ton	3,00	3,00	8.740
	BT BA GR - 2A - (Side Kit Trailer)	28m ³	6X2	57 ton	2,00	2,00	6.850
		28m ³					5.520
	RT BA GR - 2A +DL W/ 5th WHEEL - (Side Kit Trailer)	25m ³	6X2	57 ton	3,00	3,00	6.660
		25m³					5.610
	RT BA GR - 2A + DL W/ BALL HITCH - (Side Kit Trailer)	35m ³	6X4	74 ton	3,00	3,00	6.790
		35m³					6.070
		DL					2.970
	RT BA GR - 2A + DL W/ BALL HITCH - (Side Kit Trailer)	35m³	6X4	74 ton	3,00	3,00	6.450
		35m ³					6.080
		DL					2.830
	RT BA GR - 2A + DL W/ BALL HITCH - (Side Kit Trailer)	25m ³	6X4	74 ton	4,75	4,75	6.950
		25m ³					6.290
		DL					3.000
	RT BA STD AB - 2E+ DL C/ 5ª WHEEL - (Sand and Gravel)	35m³	6X4	74 ton	3,00	3,00	6.890
		35m³					6.170
		DL					2.970

*Estimated tare weight: Product with standard accessories, tires and wheels on all axles.

