

CONTAINER TRAILER

pluviadigital.com.br

**courage is
precious cargo**




- 3 manufacturing sites
- + 250,000m² of total area
- + 35 service points
- International presence
- + 80,000m² of built area



Rodovia Anhanguera, KM 108,05
Sumaré/SP - CEP: 13181-030
+5519 3770-2200
Rodovia BR-116, N° 15675
Caxias do Sul/RS - CEP: 95124-010
+5554 3771-6400

rodofortguerra.com.br



To know our **Product Line and Distributor Network**, access our website by scanning the following QR Code.

**PEACE
ON THE ROAD**



TECHNICAL FEATURES

Base

- I-beam flat base - Wide-gauge
- 2- and 3-axle mechanical suspension
- Wheel disc;
- 8.25x22.5" steel wheels;
- 1st axle air lift;
- 100% LED electrical installation
- ABS brake and Automatic brake compensator
- Lifting device
- Hinged bumper;
- Polymeric wraparound fender with mudguard
- Certified Container Couplings;
- Polymeric Toolbox
- Water tank
- Rear rubber stop
- Semi-gloss black chassis painting



COMPETITIVE DIFFERENTIALS

Wide-gauge chassis

- Increased stability and safety
- Reduced suspension and tire wear

Portfolio Diversity

- 20-, 40-, and 53-feet semi-trailers
- 20 feet + 40 feet interlink semi-trailer
- 40 feet + 40 feet sliding interlink semi-trailer

Distributor Network

- More than 35 service points throughout the country

100% LED electrical installation

- Increased durability and safety

90x90 bearing and ventilated hub

- Increased brake lining service life

One-piece steel stop + rubber stop

- Increased rear component protection

- Ideal for use on docks

Hinged bumper with reflective strip protection

- Exclusive design for reflective strip protection

Double I-beam on the gooseneck region

- Increased product resistance and service life

X-shaped structural reinforcement

- Increased stability and safety



CONFIGURAÇÕES

CONTAINER TRAILER	Couplings	TT	GCWR (ton)	External Length (mm)	Container Composition (feet)	Tare weight* (Kg)
SR BS CO - 3E	4 couplings	6x2	45 ton	7.300	1x20'	4.950
SR BS CO - 3E	4 couplings	6x2	48,5 ton	12.425	1x40'	5.860
SR BS CO - 3E	8 couplings	6x2	48,5 ton	12.425	2x20' ou 1x40'	6.180
SR BS CO - 3E	12 couplings	6x2	48,5 ton	12.425	1x20' ou 2x20' ou 1x40'	6.665
SR BS CO - 3E	12 couplings	6x2	48,5 ton	14.520 / 14.148 / 16.373	1x40' ou 1x45' ou 1x53'	7.180
BT BS CO - 3A - Fixed DT + TR	4 couplings	6x4	74 ton	8.100	1x20'	5.280
	12 couplings			12.425	1x20' ou 2x20' ou 1x40'	6.440
BT BS CO - 3E - Sliding DT + TR	12 couplings	6x4	74 ton	12.425	1x20' ou 2x20' ou 1x40'	8.090
	4 couplings			8.100	1x20'	5.280
BT BS CO - 3E - Sliding DT + TR	12 couplings	6x4	74 ton	12.425	1x20' ou 2x20' ou 1x40'	8.090
	12 couplings			12.425	1x20' ou 2x20' ou 1x40'	6.440



*Estimated tare weight: Full product with standard accessories, tires and wheels on all axles.