

courage is precious cargo





 $+ 250,000 \text{m}^2$ of total area



International presence

 $+ 80,000 m^2$ of built area





Rodovia Anhanguera, KM 108,05 Sumaré/SP - CEP: 13181-030 +5519 3770-2200 Rodovia BR-116, N° 15675 Caxias do Sul/RS - CEP: 95124-010 +5554 3771-6400

rodofortguerra.com.br



To know our Product Line and Distributor Network, access our website by scanning the following QR Code.













TECHNICAL FEATURES

Base

Chassis made of high-strength steel 8.25x22.5" steel wheel Mechanical Suspension 1st axle air lift 2" flanged kingpin 100% LED electrical installation Mechanical lifting device ABS brake and Automatic brake compensator Polymeric Toolbox Water tank Supply box (Premium Model) Aluminum side protection Polymeric wraparound fender with mudguard

Cargo Box

Cargo box made of high-strength steel Upper hinge opening rear lid Internal chains Transversal tarpaulin bows Rubber lid seal Embedded side rail between columns Front and rear mooring rivets Front and side ladder Tarpaulin: Possibility of choosing colors Cargo box: Possibility to choose colors

COMPETITIVE DIFFERENTIALS

Wide-gauge chassis Increased stability and safety Reduced suspension and tire wear **Distributor Network** More than 35 service points throughout the country Modern and functional design Roller-free lid opening **100% LED electrical installation** Increased durability and safety 90x90 bearing and ventilated hub Increased brake lining service life Embedded side rail between columns It prevents material accumulation **Electrostatic powder-painted chassis** High-performance painting, superior quality finishing Increased durability and corrosion resistance Increased resistance to impacts (rocks) Uniform coverage **UV** protection Cargo box made of high-strength steel Increased durability and resistance Supply box - standard premium model Increased comfort and convenience for the driver Dump Road Train Model with Fifth Wheel Dolly or **Ball hitch**

TABLE

DUMP	Volume	Accompl. TT	GCWR (ton)	Side Prof. (mm)	Floor Prof. (mm)	Approx. Tare Weight (Kg)
SR BA AB - 3A (1+2) - (Sand and Gravel)	20m³	4X2	43 ton	3,00	3,00	6.970
SR BA AB - 3A - (Sand and Gravel)	25m³	6X2	45 ton	4,75	4,75	7.480
SR BA AB - 3A - (Sand and Gravel)	35m³	6X2	45 ton	3,00	4,75	7.750
SR BA GR - 3A - (Side Kit Trailer)	40m ³	6X2	45 ton	3,00	3,00	7.690
SR BA GR - 3A - (Side Kit Trailer)	45m ³	6X2	48,5 ton	3,00	3,00	8.740
BT BA GR - 2A - (Side Kit Trailer)	28m ³	6X2	57 ton	2,00	2,00	6.850
	28m³					5.520
RT BA GR - 2A +DL W/ 5th WHEEL - (Side Kit Trailer)	25m ³	6X2	57 ton	3,00	3,00	6.660
	25m ³					5.610
RT BA GR - 2A + DL W/ BALL HITCH - (Side Kit Trailer)	35m³	6X4	74 ton	3,00	3,00	6.790
	35m³					6.070
	DL					2.970
RT BA GR - 2A + DL W/ BALL HITCH - (Side Kit Trailer)	35m³	6X4	74 ton	3,00	3,00	6.450
	35m³					6.080
	DL					2.830
RT BA GR - 2A + DL W/ BALL HITCH - (Side Kit Trailer)	25m³	6X4	74 ton	4,75	4,75	6.950
	25m³					6.290
	DL					3.000
RT BA STD AB - 2A + DL W/ 5th WHEEL - (Sand and Gravel)	35m³	6X4	74 ton	3,00	3,00	6.890
	35m³					6.170
	DL					2.970

*Estimated tare weight: Product with standard accessories, tires and wheels on all axles.

